

5.25" Midrange

PURE SOUND

Ultra Low Distortion
Midrange



PTT5.25M04-NFA-02 DATA SHEET

KEY SPECIFICATIONS

- ⊙ Dedicated Midrange Driver with Enhanced Efficiency
- ⊙ Negligible Force Factor Modulation
- ⊙ Ultra Low Magnetic Hysteresis Distortion
- ⊙ Utilize PURIFI's Neutral Surround Technology
- ⊙ Designed and Manufactured in Denmark

Driver size	5.25"
DC resistance, R_{DC}	3.8 Ω
Resonance freq., f_s	40 Hz
Total Q factor, Q_{ts}	0.19
Effective piston area	85 cm ²
Equivalent volume, V_{as}	12.6 L
SPL@2.83V _{rms} /1m	89.8 dB
Linear X_{max}	+/- 2.9 mm
Mechanical X_{max}	+/- 14.5 mm
IEC Power handling	TBD
Cone material	Proprietary Fibre Mix




Figure 1 Frequency Response 2.83Vrms @1m

1 Specifications

1.1 Electrical & Acoustical Parameter

Parameter		Typ	Unit
Z_n	Nominal impedance	4	Ω
Z_{min}	Minimum impedance above resonance	4.5	Ω
f_{min}	Frequency for minimum impedance	449	Hz
Z_o	Maximum impedance	143	Ω
R_{DC}	DC resistance	3.8	Ω
L_e	Voice Coil inductance @ 1kHz 0mm	0.27	mH
SPL	SPL@2.83V _{rms} /1m, 1000Hz-2800Hz, ref. 20 μ Pa (infinite baffle / 2pi)	89.8	dB
	SPL@1W(Z_{min})/1m, 1000Hz-2800Hz, ref. 20 μ Pa (infinite baffle / 2pi)	87.2	dB

Table 1 Electrical & Acoustical Parameters

1.2 T/S & Lumped Parameters

Parameter		Typ	Unit
f_s	Resonance frequency	40	Hz
Q_{ms}	Mechanical Q factor	6.9	-
Q_{es}	Electrical Q factor	0.19	-
Q_{ts}	Total Q factor	0.19	-
V_{as}	Equivalent volume	12.6	L
S_d	Effective piston area	84.9	cm ²
D	Effective piston diameter	10.4	cm
Bl	Force factor	8.1	N/A
R_{ms}	Mechanical resistance	0.47	kg/s
M_{ms}	Moving mass	13.1	g
C_{ms}	Suspension compliance	1.24	mm/N

Table 2 T/S & Lumped Parameters

1.3 Mechanical Properties

Parameter		Typ	Unit
Excursion Properties			
X_{max}	Linear excursion = (Voice Coil length - Airgap height) / 2	+/-2.9	mm
	Mechanical excursion	+/-14.0	mm
Physical Dimensions			
	Basket diameter	147	mm
	Cutout diameter	121	mm
	Mounting hole pattern diameter	138	mm
	Mounting hole diameter	4.2	mm
	Magnet diameter	100	mm
	Outer flange height	3.6	mm
	Build-in depth	75	mm
	Weight	1.75	kg
Voice Coil Properties			
	Voice Coil diameter	39	mm
	Voice Coil length	9.9	mm
	Voice Coil layers	4	-
	Airgap height	4	mm
	Winding material	CCAW	-

Table 3 Mechanical Properties

1.4 Power Handling

Parameter		Typ	Unit
	Long term maximum power (IEC268-5 18.2)	TBD	W
	Rated noise power, 100h (IEC268-5 18.4)	TBD	W

Table 4 Power Handling

1.5 Typical Performance, Graphs




Figure 2 Impedance Response @ 2.83V




Figure 3 Force Factor and Stiffness vs Voice Coil Position




Figure 4 Inductance vs Voice Coil Position




Figure 5 Axial Frequency Response @ 1m, 2.83Vrms




Figure 6 Frequency Response @ 1m, 94dB




Figure 7 Current Harmonic Distortion @ 2.83Vrms




Figure 8 Current Harmonic Distortion @ 1kHz, 0-28.3Vrms




Figure 9 Sound Pressure Harmonic Distortion @ 1m, 0-28.3Vrms




Figure 10 Intermodulation Distortion @ 250Hz 94dB, 2125Hz 94dB






Figure 11 Intermodulation Distortion @ 500Hz 94dB, 4250Hz 94dB

2 Drawings



Accuracy of Information: To the extent PURIFI ApS provides information on function and specifications, PURIFI ApS attempts to be as accurate as possible. However, PURIFI ApS does not warrant the accuracy of information on its website and other documents as accurate, complete, reliable, current, or error-free. All data and information in the Data Sheet are subject to change.